



ЛОКАТОР-К ООД

1404 София, ж.к. "Гоце Делчев", бл. 258, вх. А www.lokatork.com
тел.: (+ 359 2) 9621881; 9622138, факс: 9622139, E-mail: lokator@dir.bg



ДИГИТАЛЕН МУЛТИМЕТЪР модел PeakTech P3425



Digital-Multimeter with Bargraph, 3 5/6-digit

Multimeter designed as per the highest safety standard CAT III 1000V / CAT IV 600V and TÜV/GS-approved featuring modern style, integrated protection frame. The 3 5/6-digit LCD-display (max. 6000) with function symbols, 61-segment analogue bargraph and backlight guarantee exact results.

3 5/6-digit, 21 mm LCD-display, max. 6000

Continuity- and diode test

Data Hold, MIN/MAX- Hold

Relative function

Reset-button

LPF-function (Low Pass Filter) prevents from high harmonic influences to AC Voltage and Current measurements

Auto- and manual range selection

Duty cycle

Auto power off

Safety: EN 61010-1/EK-1; CAT III 1000V/CAT IV 600V

Accessories: test leads, carrying case, type K-temperature probe, temp.-adaptor, battery and operation manual

DCV	600 mV/6/60/600/1000 V; 0,1 mV; +/- 0,8 % + 3 dgt.
ACV	6/60/700 V; +/- 1 % + 4 dgt. / frequency range: 50 Hz ... 2 kHz
DCA	600µA/6/60/600mA/10 A; 0,01 µA; +/- 1,2 % + 4 dgt.
ACA	600µA/6/60/600mA/10 A; 0,01 µA; +/- 1,5 % + 3 dgt. / frequency range: 50 Hz ... 2 kHz
Ohm	600 Ω/6/60/600kΩ/6/60MΩ; 0,01 Ω; +/- 1,0 % + 2 dgt.
Capacitance	40/400nF/4/40/440µF; 1nF; +/- 3,5 % + 3 dgt.
Frequency	100/1000 Hz/10/100 kHz/10MHz; 1 Hz; +/- 0,2 % + 3 dgt.
Temperature	-10°C...+ 700°C ; 1°C ; +/- 3 % + 3 dgt.
Operation voltage	4 x 1,5 V (AA) batteries
Dimensions (WxHxD)	102 x 205 x 58 mm
Weight	390 g
EAN-13	4250569400926